

Sprockst Size					600SS to VIN 001852 & 600M to VIN 002961	Later 600s	620		
yellow is standard gearing					32/73 (2.28:1)	31/62 (2:1)	33/61 (1.85)		
Fr	Rr	Fr	Rr	order code	Ratio	mph for 32/73 @ 9000rpm	mph for 31/62 @ 9000rpm	mph for 33/61 @ 10000rpm	skidlids (ss583)
14	45				3.21	90.4	103.1	123.9	
		15	48	236-520-48	3.20	90.8	103.5	124.5	
14	44				3.14	92.4	105.4	126.7	
		15	47	236-520-47	3.13	92.7	105.7	127.1	
14	43				3.07	94.6	107.9	129.7	
		15	46	236-520-46	3.07	94.7	108.0	129.9	
14	42	15	45	236-520-45	3.00	96.8	110.4	132.8	
		15	44	236-520-44	2.93	99.0	113.0	135.8	
14	41				2.93	99.2	113.1	136.0	
		15	43	236-520-43	2.87	101.3	115.6	139.0	Cadwell Woodlands, Donny (wet)
14	40				2.86	101.7	116.0	139.4	Cadwell Woodlands, Donny (wet)
		15	42	236-520-42	2.80	103.7	118.3	142.3	Pembrey, Donny(dry), Brands Indy, Cadwell GP
14	39				2.79	104.3	118.9	143.0	
		15	41	236-520-41	2.73	106.3	121.2	145.7	Castle Combe, Snetterton
14	38				2.71	107.0	122.1	146.8	
		15	40	236-520-40	2.67	108.9	124.3	149.4	
		15	39	236-520-39	2.60	111.7	127.4	153.2	
		16	41	236-520-41	2.56	113.4	129.3	155.4	
		15	38	236-520-38	2.53	114.7	130.8	157.2	
		16	40	236-520-40	2.50	116.2	132.5	159.3	
		15	37		2.47	117.8	134.3	161.5	
		16	39	236-520-39	2.44	119.2	135.9	163.4	
		15	36		2.40	121.0	138.1	166.0	

Cadwell Woodlands, Donny (wet)
Cadwell Woodlands, Donny (wet)
Pembrey, Donny(dry), Brands Indy,
Cadwell GP

Castle Combe, Snetterton